PEERLESS M24T & M27T PLATE AND TRAY FORMING MACHINES



M24T & M27T Vertical Lift Paperboard Roll Stand

- Integral to the machine line incorporating pull roll/dancer arm assembly for consistent tension of the paperboard feeding into the decurl and cut/ score sections of the machine.
- Heavy-duty hydraulic cylinder utilized for vertical lifting and manual hand wheel system used for lateral shifting of paperboard rolls results in quick roll changeover times.
- Pneumatic or mechanical core chuck assemblies available.




M24T & M27T Cut & Score Section

- Easy access decurl unit assists in removing any up or down curl in the paperboard for smooth and consistent feed ups.
- Photoelectric eye utilized in conjunction with a servo motor feed drive system results in consistent feed ups and a print-to-cut accuracy of +/- .015" or .38 mm.
- Precision heavy-duty mechanical toggle system and four-pin die set insures accurate, and repeatable steel rule die cutting and prescoring capability.
- Steel rule cut/score die design utilized for reduced tooling costs and quick die changeover capability.
- 75 tons (665 kN) capacity insures quality die cutting and prescoring for deep draw paperboard tray production.

M24T & M27T Forming Section

- Adjustable forming head dwell and stroke capability allows machine settings to be tailored to each specific product resulting in optimum quality and production speeds.
- Precision heavy-duty mechanical toggle system and four-pin die set insures accurate and repeatable forming die performance resulting in high quality products.
- 24 tons (210 kN) capacity provides the required pressure for quality forming of deep draw large trays.
- Forming dies are installed and removed as a set to speed changeovers.



M24T & M27T Counter-Stacker Unit

- Integral to the machine line. Individual belted lanes transfer the formed product from the forming dies into the stacking and counting section.
- Design allows tall product stacks and offers space for presentation of multiple stacks prior to operator.





M24T & M27T Hydraulic Power Unit

• Compact Unit provides power to roll stand and machine.

M24T & M27T Main Panel & Control System

• P.C. controls support operator interface, temperature, feed, and cut-score/forming motion control. Production programs are easily stored and retrieved.





M24T & M27T Safety Systems

- Interlocked guards stop both reciprocating head motions and hydraulic pump motor when opened.
- All electricals conform to applicable worldwide standards



Peerless Machine & Tool Corporation 1804 W. 2nd Street

P.O. Box 385 Marion, IN 46952

Phone: 765-662-2586 Fax: 765-662-6067

E-Mail: peerless@peerlessmachine.com Website: www.peerlessmachine.com Peerless Machine & Tool, GmbH Arnold-Sommerfeld-Ring 2 52499 Baesweiler Germany

Phone: INT+ 49-2401-4071
Fax: INT+ 49-2401-7037
E-Mail: info@peerlessmachine.de
Website: www.peerlessmachine.com